





Functions:

KC

66

(')

- Memory for 100 items with alphanumerical code.
 - Classification or verification by weight with viewing in 3 bright colours.
 - Piece counter function with weight memory by unit for 100 items.
 - 4 Autohold levels for weighing large-size objects.
 - Memory zero for weighing tanks and silos.
 - Port for barcode scanner.
 - Accumulation of weighings with aggregation.
 - Automatic, normal or set tare.
 - Memory for 20 preset tares.
 - Ticket printing.



Adaptable

Can be hung from the wall without the need for a support, or installed on a column.

INDICATORS



Protection against liquids and dust

Designed for working in humid or dusty environments. With IP-65 protection.



Weight verification

The visor changes colour to indicate whether the weight is above (red colour), below (yellow colour) or within (green colour) of the set range.

| Model | КЗі |
|----------------------------------|-----------------------------------------------|
| Reference | 6171 |
| Resolution | 100,000 div. |
| Weight ranges | =<2 |
| Linearity | 10 points |
| Calibration weight | Selectable |
| Weighing units | g(kg), lb, oz |
| Piece counter quantities | 10, 20, 30, 50, 100 |
| Display | Backlit LCD |
| Segments | 6 digits |
| Digit height (mm) | 25 |
| Connectivity | RS 232-C, 3-relay output (opt.), Wi-Fi (opt.) |
| Material | ABS |
| Sealing protection | IP-65 |
| Power | 230 V / 50 Hz (Euro) 11 V AC |
| Battery duration | 30 / 60 hours |
| Working temperature | +5°C / +35°C |
| External dimensions (mm) | 225 x 190 x 94 |
| Total net weight (kg) | 2.5 |
| Packaging dimensions (mm) | 325 x 235 x 165 |
| Total weight with packaging (kg) | 3.3 |
| RRP (€) | , |

| Ref. | Options | RRP (€) |
|-------|-----------------------|---------|
| 32330 | 3-relay output | , |
| 32277 | RS-232 second output | , |
| 3776 | Wireless K connection | , |



Printing of results

Connection with our printers, with and without (wireless) cable. Prints three initial lines and one at ticket end, including our Z3 THS software for data input from PC. With our Q2 labelling machine it prints the data in an adhesive label format. Connects with our remote display via cable or wireless.



USB Direct, what you always wanted

With our direct cable between the indicator and your PC or MAC, the weighing data will appear in any application or document you have open. Without intermediate software, without installation, simple and effective.

| Ref. | Accessories | RRP (€) |
|-------|------------------------------------|---------|
| 32332 | Tare pedal | , |
| 5263 | RD3 repeater indicator (RS-232) | , |
| 6950 | RD3W repeater indicator (Wireless) | , |
| 70814 | Q2 labelling machine | , |
| 70034 | PR4 printer (RS-232) | , |
| 70035 | PR4W printer (Wireless) | , |
| 70036 | PR6 printer (RS-232) | , |
| 70037 | PR6W printer (Wireless) | , |
| 4877 | Virtual Key software for PC | , |
| 32278 | Stainless steel U wall support | , |
| 61084 | Direct K USB cable | , |
| 33205 | RS-232 cable to RD3 or PC K, 1.5 m | , |
| 3738 | RS-232 cable to RD3 or PC K, 4 m | , |
| 32294 | RS-232 cable to K Printer | , |

225 mm

External dimensions (mm)

K3i

94 mm

190 mm

More information

Product sheet:



http://gram-group.com/product/ gram-k3i-indicator/

